

# HEAVY DUTY SILAGE FORK

<http://tiny.cc/silagefork>


## FEATURES & BENEFITS

- Heavy duty frame (except mod. 80)
- Versatile and efficient
- Replaceable teeth
- Compact model, which is well suited for silage distributing in small and confined places

The multi-purposed silage fork, in combination with the frame top hydraulic clamp, makes moving loose or baled silage safe and easy. The extra strength framework allows heavy loads, like round bales, to be safely and effectively moved. The lower fork teeth are easily removed and replaced when worn (except mod. 80).



Model	Width	Teeth length	Nr. of teeth	Max load capacity*	Weight	Code
80**	80 cm (31.5 in)	48 cm (18.9 in)	5	300 kg (660 lbs)	67 kg (148 lbs)	<b>C895061</b>
95	95 cm (37.4 in)	60 cm (23.6 in)	6	600 kg (1322 lbs)	88 kg (194 lbs)	<b>C890355</b>
120	120 cm (47.3 in)	60 cm (23.6 in)	8	800 kg (1763 lbs)	110 kg (242 lbs)	<b>C890356</b>
150	150 cm (59 in)	60 cm (23.6 in)	9	900 kg (1984 lbs)	130 kg (287 lbs)	<b>C890357</b>

(\*) verify the lifting capacity of the machine (\*\*) equipped by flat face single lines connections

Compatibility	1.1	2.3	4.2	5.2	5.3	6.3	7.2	8.4	8.5	11.6	11.9	EZ5	EZ7 EZ8
Model													
80													
95													
120													
150													

Very compatible

Compatible

Not compatible